



Current Transformers



Window Diameter: 1.23"
Continuous Thermal Rating: 1.33 at 30 C. amb.;
1.0 at 55 C. amb. Average.

Application: Ammeters, Wattmeters and Relays.
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.
Fully encapsulated.



Standard 5 amp secondary, others available.



12503RW**



12503SB**



12503SH**

To order, please complete the model number with the appropriate suffix.
eg. CT12503RW100:5A

- Flexible leads are UL 3173 125°C.
- CSA approved, # 16 AWG 24" long.
Nonstandard length to be specified.
- Terminals are brass No. 10-32 UNC.
- Optional mounting bracket 12503MBK.
- Approximate weight 10.5 lb.
- Additional ratios available.

Model nbr.	Catalogue nbr. Suffix	Current Ratio	Relay Class	ANSI Metering Class @ 60Hz				
				BO.1	BO.2	BO.5	BO.9	B1.8
12503RW	-100	100:5	C10	0.6	1.2	2.4	2.4	2.4
12503SB	-150	150:5	C10	0.3	0.6	1.2	1.2	1.2
12503SH	-200	200:5	C20	0.3	0.3	0.6	1.2	1.2
	-250	250:5	C20	0.3	0.3	0.3	0.6	0.6
	-300	300:5	C50	0.3	0.3	0.3	0.3	0.3
	-400	400:5	C50	0.3	0.3	0.3	0.3	0.3
	-500	500:5	C50	0.3	0.3	0.3	0.3	0.3
	-600	600:5	C50	0.3	0.3	0.3	0.3	0.3
	-750	750:5	C50	0.3	0.3	0.3	0.3	0.3
	-800	800:5	C50	0.3	0.3	0.3	0.3	0.3
	-1000	1000:5	C100	0.3	0.3	0.3	0.3	0.3
	-1200	1200:5	C100	0.3	0.3	0.3	0.3	0.3
	-1500	1500:5	C100	0.3	0.3	0.3	0.3	0.3
	-1600	1600:5	C50	0.3	0.3	0.3	0.3	0.3
	-2000	2000:5	C50	0.3	0.3	0.3	0.3	0.3